

## Continuous HP/ kW Rating

Diesel Engines - Air-cooled/ Oil cooled															
Series	Model		Rated RPM	Cyl	1500	1800	2000	2200	2400	2600	2800	3000	3200	3400	3600
AC/OC	AC60	HP	3,600	1	-	-	-	4.0	4.2	4.5	4.5	5.0	5.2	5.5	5.6
		kW			-	-	-	3.0	3.1	3.4	3.4	3.7	3.9	4.1	4.2
	OC60	HP	3,600	1	-	-	-	4.0	4.2	4.5	4.7	5.0	5.2	5.5	5.6
		kW			-	-	-	3.0	3.1	3.4	3.5	3.7	3.9	4.1	4.2
	OC95	HP	3,600	1	-	-	-	6.0	6.5	7.0	7.4	7.7	8.1	8.3	8.3
		kW			-	-	-	4.5	4.8	5.2	5.5	5.7	6.0	6.2	6.2
Diesel Engines - Vertical Water-cooled															
NSM	Z482	HP	3,600	2	-	5.6	6.2	6.8	7.4	8.0	8.7	9.3	9.7	10.3	10.8
		kW			-	4.2	4.6	5.1	5.5	6.0	6.5	6.9	7.2	7.7	8.1
	Z602	HP	3,600	2	-	7	8	8.4	9.1	9.8	10.5	11.2	11.8	12.6	13.5
		kW			-	5.0	5.6	6.3	6.8	7.3	7.8	8.4	8.8	9.4	10.1
	D722	HP	3,600	3	-	8	9	10.3	11.2	12.1	13.0	13.8	14.7	15.5	16.3
		kW			-	6.3	6.9	7.7	8.4	9.0	9.7	10.3	11.0	11.6	12.2
D902	HP	3,600	3	-	10	11	12.5	13.8	14.8	16.0	17.0	17.7	19.1	20.4	
	kW			-	7.5	8.4	9.3	10.3	11.0	11.9	12.7	13.2	14.2	15.2	
05	D905	HP	3,000	3	9	11	12	12.9	14.0	15.1	16.0	17.0	-	-	-
		kW			6.6	7.8	8.7	9.6	10.4	11.3	11.9	12.7	-	-	-
	D1105	HP	3,000	3	11.4	13.6	15.0	16.5	17.9	19.2	20.6	22.0	-	-	-
		kW			8.5	10.1	11.2	12.3	13.3	14.3	15.4	16.4	-	-	-
	D1105-T	HP	3,000	3	-	16.3	18.2	20.3	22.2	24.0	25.9	27.7	-	-	-
		kW			-	12.2	13.6	15.1	16.6	17.9	19.3	20.7	-	-	-
V1505	HP	3,000	4	13.9	17.9	19.9	21.8	23.6	25.3	27.1	29.0	-	-	-	
	kW			10.4	13.3	14.8	16.3	17.6	18.9	20.2	21.6	-	-	-	
V1505-T	HP	3,000	4	18.7	22.5	25.0	27.4	29.7	32.0	34.1	36.5	-	-	-	
	kW			13.9	16.8	18.6	20.4	22.1	23.9	25.4	27.2	-	-	-	
03	D1403	HP	2,800	3	14.3	16.9	18.5	20.1	21.7	23.3	25.0	-	-	-	-
		kW			10.7	12.6	13.8	15.0	16.2	17.4	18.6	-	-	-	-
	D1703	HP	2,800	3	17.2	20.2	22.3	24.3	26.2	28.1	30.0	-	-	-	-
		kW			12.8	15.1	16.6	18.1	19.5	21.0	22.4	-	-	-	-
	D1803	HP	2,800	3	19.7	23.3	25.4	27.0	28.7	30.3	30.9	-	-	-	-
		kW			14.7	17.4	18.9	20.1	21.4	22.6	23.0	-	-	-	-
	V1903	HP	2,800	4	19.5	23.0	25.3	27.5	29.7	31.8	34.0	-	-	-	-
		kW			14.5	17.2	18.9	20.5	22.1	23.7	25.4	-	-	-	-
	V2203	HP	2,800	4	23.0	27.1	29.7	32.4	35.0	37.5	40.0	-	-	-	-
		kW			17.2	20.2	22.1	24.2	26.1	28.0	29.8	-	-	-	-
	V2003-T	HP	2,800	4	27.5	32.5	36.2	39.7	42.9	45.9	48.6	-	-	-	-
		kW			20.5	24.2	27.0	29.6	32.0	34.2	36.2	-	-	-	-
V2403	HP	2,700	4	27.0	31.9	35.2	36.9	38.5	39.6	40.1 @ 2700		-	-	-	
	kW			20.1	23.8	26.2	27.5	28.7	29.5	29.9 @ 2700		-	-	-	
V2403-T	HP	2,700	4	27.8	33.6	36.9	41.0	44.2	46.7	48.0 @ 2700		-	-	-	
	kW			20.7	25.1	27.5	30.6	33.0	34.8	35.8 @ 2700		-	-	-	
V3	V3300	HP	2,600	4	36.5	43.4	47.5	51.8	55.6	59.1	-	-	-	-	-
		kW			27.2	32.4	35.4	38.6	41.5	44.1	-	-	-	-	-
	V3300-T	HP	2,600	4	44.5	52.6	57.8	63.0	67.5	72.1	-	-	-	-	-
		kW			33.2	39.2	43.1	47.0	50.3	53.8	-	-	-	-	-
	V3800	HP	2,600	4	40.0	48.0	54.0	58.0	64.0	68.5	-	-	-	-	-
		kW			29.8	35.8	40.3	43.3	47.7	51.1	-	-	-	-	-
V3800-T	HP	2,600	4	52.5	62.0	67.0	72.5	77.5	82.5	-	-	-	-	-	
	kW			39.1	46.2	50.0	54.1	57.8	61.5	-	-	-	-	-	

\*25°C ambient temperature, 30% relative humidity at 100 meters altitude